

MAHAVIR INDUSTRIES

(Since 1979)
(Manufacturer & Exporter of Dyestuff & Organic Pigments)

SPECIFICATION OF MAHASOL YELLOW 4033

PRODUCT DESCRIPTION	
C.I. Name	Solvent Yellow 33
C.I. No.	47000
CAS Registry No.	8003-22-3
EU No.	232-318-2
Melting Point (°C)	240°C
Chemical Formula	C ₁₈ H ₁₁ NO ₂
Density (g/cm ³)	1.46

APPLICATION (● - Superior ○ - Applicable X - Not Recommend)	
PS	●
HIPS	●
ABS	●
PC	●
RPVC	●
PMMA	●
AS	●
PET	●
PA6	X

MASS TONE	TINT TONE
	

Solubility at 20°C(g/l)	
Acetone	0.2
Butyl Acetate	0.2
Methylbenzene	0.6
Dichloromethane	0.3
Ethylalcohol	0.1

STANDARD PACKAGING	
25 Kgs / 20 Kgs / 10 Kgs	Paper Bags / HDPE Bags
25 Kgs / 20 Kgs	Fiber Drum / Plastic Drum
Big Bags type	On Request

Description:

Solvent Yellow 33 Solvent Yellow 33 is a greenish yellow dye with high color strength. It has excellent heat resistance and light resistance, good migration resistance and high tinting strength with wide application. Solvent Yellow 33 is used for coloring for plastics, PS, ABS, PMMA, PC, PET, polymer

Light Fastness: 8

Consist of 1st to 8th grade, and the 8th grade is superior, the 1st grade is bad.

The heat resistance in PS can reach to 300°C

Degree of Pigmentation: 0.05% Dyes+0.1% Titanium Dioxide

Our product specific end application information are based upon our current knowledge. They are presented without any representation or warranty concerning the suitability, performance or correctness of the product for a particular application or use. Significant variations can occur between test results and results obtained in actual use. We strongly advise that the customer test the product in the specific intended application under conditions expected during use.