

SPECIFICATION OF MAHAFIX MAGENTA MB

PRODUCT DESCRIPTION	
Brand Name	Mahafix Magenta MB
C.I. Name	Reactive Violet 13
Affinity	High
Solubility at 30°C	80

FASTNESS PROPERTIES	
Day Light ISO	3-4
Washing ISO 4	3-4
Perspiration	
Alkaline	3-4
Acidic	5
Hypochlorite Bleach	1

1%	4%

SUITABILITY	
Exhaust at R.T.	Suitable
Printing Steam	Suitable
Printing Silicate	Not Suitable

STANDARD PACKAGING	
HDPE Bags	25 Kgs
Carton Box	25 Kgs

Our product specific end application information are based upon our current knowledge. They are presented without any representation or warranty concerning the suitability, performance or correctness of the product for a particular application or use. Significant variations can occur between test results and results obtained in actual use. We strongly advise that the customer test the product in the specific intended application under conditions expected during use.

FOR, MAHAVIR INDUSTRIES



PARTNER



REGISTERED OFFICE

1007-1008, DEV ATELIER COMPLEX, NR. SEEMA HALL, PRAHLADNAGAR ROAD, SATELLITE, AHMEDABAD - 380015, GUJARAT INDIA.

FACTORY

C-1/58 PHASE-2 GIDC ESTATE, VATVA - AHMEDABAD - 382445, GUJARAT INDIA.
 (O) +91 79 - 4008 5720 (W) www.mahavirdyes.com (E) info@mahavirdyes.com