

SPECIFICATION OF MAHAFIX YELLOW FG

PRODUCT DESCRIPTION	
Product Name	Mahafix Yellow FG
C.I. Name	Reactive Yellow 42
Substantivity	High
Solubility at 30°C	100
Dischargeability	Good

FASTNESS PROPERTIES			1%	4%
Day Light ISO	4			
Washing ISO 4	5			
Perspiration				
Alkaline	5			
Acidic	5			
Hypochlorite Bleach	1			

SUITABILITY	
Printing Steam	Suitable
Printing Silicate	Fully Suitable
One bath pad batch	Suitable
One bath pad - dry steam	Suitable
Exhaust 40°C & 60° C	Not Suitable

STANDARD PACKAGING	
HDPE Bags	25 Kgs
Carton Box	25 Kgs

Our product specific end application information are based upon our current knowledge. They are presented without any representation or warranty concerning the suitability, performance or correctness of the product for a particular application or use. Significant variations can occur between test results and results obtained in actual use. We strongly advise that the customer test the product in the specific intended application under conditions expected during use.

FOR, MAHAVIR INDUSTRIES




PARTNER



REGISTERED OFFICE

1007-1008, DEV ATELIER COMPLEX, NR. SEEMA HALL, PRAHLADNAGAR ROAD, SATELLITE, AHMEDABAD - 380015, GUJARAT INDIA.

FACTORY

C-1/58 PHASE-2 GIDC ESTATE, VATVA - AHMEDABAD - 382445, GUJARAT INDIA.
 (O) +91 79 - 4008 5720 (W) www.mahavirdyes.com (E) info@mahavirdyes.com